PERMIT NO. _____

APPLICATION / SWIMMING POOL PERMIT

Property Owner _____ Phone No. _____

Address _____

Property Location _____

Contractor _____ Twp License No _____

Address _____ Phone No. _____

_____

1. SIZE: Max Length _____ Max Width _____ Max Depth _____

2. TYPE: Inground ☐ Above Ground ☐

3. Diving Board?: Yes ☐ No ☐

***SEE REVERSE OF THIS APPLICATION FOR IMPORTANT INFORMATION**

4. LOCATION ON LOT: Include plot plan showing property lines, setback distances and location of the following improvements (provide 2 complete sets of construction documents and show pool cross section): a) All existing buildings; b) Well(s); c) Septic system(s); tanks; drainfields; d) Driveways; e) The location of the pool, showing the distance from all property lines and improvements; **F)** The location of all pool equipment (filter, decks, walkways, sliding boards, etc.)

5. Is there a permanent electric supply line to the pool or filter? Yes ☐ No ☐
   (If yes, give details)
   a) Type of wire _____ Length _____ Depth _____
   b) Circuit protector 15 Amp ☐ 20 Amp ☐ 30 Amp ☐
   c) Is there a ground fault interceptor on the service line? Yes ☐ No ☐
   d) Contractors name _____ Phone No. _____

6. Will there be any overhead electric wires directly above the pool or within 18 feet of the water surface? Yes ☐ No ☐

7. Perimeter fence; Type _____ Height _____ (48" minimum)
   (Self-locking (child proof) gate required

_____ Cost of Improvement

_____ Application Date

_____ Signature of Applicant

_____ Permit Fee

_____ Issue Date

Approved _____
Denied _____

421.10 ENCLOSURES FOR PRIVATE SWIMMING POOLS, SPAS AND HOT TUBS: Private swimming pools, spas and hot tubs shall be enclosed in accordance with Sections 421.10.1 through 421.10.4 or by other approved barriers.

421.10.1 OUTDOOR PRIVATE SWIMMING POOL: An outdoor private swimming pool, including an in-ground, above-ground or on-ground pool, hot tub or spa shall be provided with a barrier which shall comply with the following:

1. The top of the barrier shall be at least 48 inches (1219 mm) above finished ground level barrier shall be 2 inches (51 mm) measured on the side of the barrier which faces away from the swimming pool. The maximum vertical clearance between finished ground level and the barrier shall be 2 inches (51 mm) measured on the side of the barrier which faces away from the swimming pool. Where the top of the pool structure is above finished ground level, such as an above ground pool, the barrier shall be at finished ground level, such as the pool structure, or shall be mounted on top of the pool structure. Where the barrier is mounted on top of the pool structure, the maximum vertical clearance between the top of the pool structure and the bottom of the barrier shall be 4 inches (102 mm).

2. Openings in the barrier shall not allow passage of a 4 inch (102 mm) diameter sphere.

3. Solid barriers shall not contain indentures or protrusions except for normal construction tolerances and tooled masonry joints.

4. Where the barrier is composed of horizontal and vertical members and the distance between the top of the horizontal members is less than 45 inches (1143 mm), the horizontal members shall be located on the swimming pool side of the fence. Spacing between vertical members shall not exceed 1¾ inches (44 mm) in width. Decorative cutouts shall not exceed 1¾ inches (44 mm) in width.

5. Where the barrier is composed of horizontal and vertical members and the distance between the tops of the horizontal members is 45 inches (1143 mm) or more, spacing between vertical members shall not exceed 4 inches (102 mm). Decorative cutouts shall not exceed 1¾ inches (44 mm) in width.

6. Maximum mesh size for chain link fences shall be 1¼ inch (32 mm) square unless the fence is provided with slats fastened at the top or the bottom which reduce the openings to not more than 1¾ inches (44 mm).

7. Where the barrier is composed of diagonal members, such as a lattice fence, the maximum opening formed by the diagonal members shall be not more than 1¾ inches (44 mm).

8. Access gates shall comply with the items 1 through 7 of Section 421.10.1, and shall be equipped to accommodate a locking device. Pedestrian access gates shall open outwards away from the pool and shall be self-closing and have a self-latching device. Gates other than pedestrian access gates shall have a self-latching device. Where the release mechanism of the self-latching device is located less than 54 inches (1372 mm) from the bottom of the gate: (a) the release mechanism shall be located on the pool side of the gate at least 3 inches (76 mm) below the top of the gate: (b) the gate and barrier shall not have an opening greater than ½ inch (13 mm) within 18 inches (457 mm) of the release mechanism.

9. Where a wall of a dwelling serves as part of the barrier, one of the following shall apply:

   9.1 All doors with direct access to the pool through that wall shall be equipped with an alarm which produces an audible warning when the door and its screen, if present, are opened. The alarm shall sound continuously for a minimum of 30 seconds immediately after the door is opened. The alarm shall have a minimum sound pressure rating of 85dBA at 10 feet (3048 mm) and the sound of the alarm shall be distinctive from other household sounds such as smoke alarms, telephones and door bells. The alarm shall automatically reset under all conditions. The alarm shall be equipped with manual means, such as touchpads or switches, to deactivate temporarily the alarm for a single opening from either direction. Such deactivation shall last for not more than 15 seconds. The deactivation touchpads or switches shall be located at least 54 inches (1372 mm) above the threshold of the door.

   9.2 The pool shall be equipped with an approved power safety cover.

10. Where an above-ground pool structure is used as a barrier or where the barrier is mounted on top of the pool structure, and the means of access is a fixed or removable ladder or steps, the ladder or steps shall be surrounded by a barrier which meets the requirements of items 1 through 9 of Section 421.10.1. A removable ladder shall not constitute an acceptable alternative to enclosure requirements.